


LONY



S
Y
N
T
H
E
T
I
C



HS CODE

84798997

CARTON SIZE / PCS.

60 x 36 x 35 cm / 1

AET N° PPE-3460-24135-Cert

ANCCP Certification Agency S.r.l. N°0302


Via dello Struggino, 6
57121 LIVORNO (LI) - Italy

MODULE D FI14/14003.12

SGS Fimko Oy, N°0598

Takomotie 8,
380 Helsinki, FINLAND

REF.	FA 20 401 20R
LG. 	18 m
KG	MAX. 140 KG
CE	EN 360:2023, EN 1496:2017 Class B
MAT. 	Polyamide 6 - 30% fiber glass
	Ø 6.0 mm Synthetic
	 FA 50 225 23B / FA 50 203 20 with fall indicator
	x2
R(kN)	15 kN
	NO
	10.61 KG

LG. 	MAT. 	
Longueur Poids maxi utilisateur Length Max. user weight Longitud Peso máximo del usuario Lunghezza Peso Max. dell'utente Länge Höchstgewicht des Benutzers	Matière carter / câble Material of casing / wire rope Material cárter / cable Material dei carter / Cavo Material Gehäuse / Seil	Matière connecteur haut / connecteur bas Material of top connector / bottom connector Material conector alto / conector bajo Materiale connettore alto / connettore basso Material oberes / unteres Verbindungselement
		
Nombre d'émerillons Number of swivels Cantidad de eslabones giratorios Numero di tornichetti Anzahl der Wirbel	Homologué pour le travail à proximité d'arêtes vives Approved for work near sharp edges Homologado para trabajo cerca de aristas vivas Omologato per lavoro in prossimità di spigoli vivi Zugelassen für Arbeiten in der Nähe scharfer Kanten	